



## **SILVER STATE SYNTHETIC EURO** **SAE 5W-30 LL-01**

**SILVER STATE SYNTHETIC EURO 5W-30 LL-01** is our most advanced and powerful engine oil to date. This top tier, “High SAPS” formulation supplies the reinforcement needed for today’s demanding, higher RPM and output engines that operate under increased pressures requiring lower viscosity oils with superior levels of protection. Silver State LL-01 is designed for high performance gasoline engines or diesel engines without particulate filters. Please refer to owner’s manual as this robust formula may exceed diesel particulate filter limits, which would require Silver State LL-04.

### **Suitable For Use In These Applications:**

<b>ACEA A3/B4-12 (2012)</b>	<b>Volkswagen VW50200 (2005)</b>	<b>Ford WSS-M2C913-C</b>
<b>ACEA A5/B5-12 (2012)</b>	<b>Volkswagen VW50500 (2005)</b>	<b>Opel GM-LL-B-025</b>
<b>ACEA A5/B5-10 (2010)</b>	<b>Renault RN0700 / RN0710</b>	<b>Opel GM-LL-A-025</b>
<b>ACEA A3/B4-10 (2010)</b>	<b>BMW Longlife-01*</b>	
<b>API SN / SM / CF</b>	<b>Porsche</b>	
<b>MB- 229.5 / 229.3 / 226.5</b>	<b>PSA Peugeot Citroën B712296</b>	

\*Same chemistry as Silver State Fully Synthetic Euro SAE 5W-40 LL-01.

**SILVER STATE FULLY SYNTHETIC MOTOR OILS provide an extra margin of safety for car owners who occasionally exceed prescribed drain intervals.**

Warranty protection requires following manufacturers recommended drain intervals, viscosity grade and product quality.

TYPICAL PROPERTIES	
<b>SAE GRADE</b>	<b>5W30*</b>
<b>SPECIFIC GRAVITY @ 60 °F</b>	<b>.85</b>
<b>FLASH, °C</b>	<b>210</b>
<b>POUR POINT, °F</b>	<b>-34</b>
<b>VISCOSITY:</b>	
<b>cSt @ 40 °C</b>	<b>86</b>
<b>cSt @ 100 °C</b>	<b>12.1</b>
<b>VISCOSITY INDEX</b>	<b>171</b>
<b>CCS, Cp MAX</b>	<b>6600</b>
<b>@ (°C)</b>	<b>-30</b>