



RUGGED™ UNIVERSAL TRACTOR FLUID (UTF)

Rugged™ UTF is a premium quality fluid designed to meet the demanding requirements of the modern tractor that uses the same fluid for transmission, differential, wet brake, and hydraulic systems.

APPLICATIONS:

- For use in tractors where a combination fluid for transmissions, differentials, and hydraulics is specified.
- For all hydraulic oil applications in farm equipment.

Meets or exceeds these requirements:

- CATERPILLAR TO-2
- LANDINI
- SUNDSTRAND HYDRAULICS
- STEIGER
- AGCO/DEUTZ-ALLIS
- KUBOTA
- VERSATILE
- FIAT-HESSTON
- WHITE FARM Q1826, Q1705, Q1722, Q1766, Q1802
- ALLISON C-4
- DENISON HF-O
- VICKERS 1-286-S AND M2950S
- JOHN DEERE QUATROL tm, J21, **J20C**, J14A, J303
- FORD NEW HOLLAND M2C134-D, M2C41-B, M2C48-B, M2C53-A, M2C134- A/B/C, M2C86B
- MASSEY FERGUSON M1135, M1143, M1141, M1110, M1127, M1129A
- CASE INTERNATIONAL JIC-145/JIC-143, JIC185/MS1204, MS1230, MS1210, MS 1209,1207, MS1205/1206, B-6, B-5

ADVANTAGES:

This one product satisfies the requirements of most JOHN DEERE, MASSEY FERGUSON, ALLIS CHALMERS, WHITE, and other tractor manufacturers of farm equipment using a combination fluid.

TYPICAL PROPERTIES		
Gravity, °API	ASTM D-287	27.0
Flash Point, °F	ASTM D-92	385
Viscosity:		
SUS @ 100 °F		275
SUS @ 210 °F		56.7
cSt @ 40 °C	ASTM D-445	59.4
cSt @ 100 °C	ASTM D-445	9.4
Viscosity Index	ASTM D-2270	140
Sulfated Ash, wt. %	ASTM D-874	1.13
Rust Test ASTM		PASS
Pour Point, °F	ASTM D-97	-30

A SUPERIOR PRODUCT BY COLORADO PETROLEUM 10-04-2024 JDS

Product Code: RGUTF