



Silver State Fully Synthetic SAE 0W-40

Silver State Fully Synthetic SAE 0W-40 is made with synthetic base stocks and a robust additive package that provides the maximum level of protection against engine wear, rust, corrosion, oxidation and thermal breakdown. It also includes a special viscosity index improver and pour point depressant designed to provide a high degree of protection under severe temperature and operating conditions.

Silver State Fully Synthetic SAE 0W-40 is specially formulated for use in European vehicles calling for an SAE 0W-40 motor oil. These vehicles include BMW, Mercedes-Benz, Porsche, Renault and Volkswagen and other vehicles.

Specifications:

- Surpasses API service classification SN.
- Meets or exceeds the U.S. and Japanese (JASO) requirements for valve train wear protection.
- Meets or exceeds Energy Resource Conserving,
- Exceeds car manufacturer's requirements for maintaining warranty validity.
- Meets or exceeds the latest automobile manufacturer's recommendations.

Performance Requirements:

Silver State Fully Synthetic SAE 0W-40 is suitable for use in these applications:

ACEA A3/B4, BMW Longlife-01, Mercedes-Benz MB 229.3, MB 229.5, Porsche A40, Renault RN0710, RN0700, Volkswagen VW 502 00, VW 505 00.

TYPICAL PROPERTIES	
SAE GRADE	0W40
SPECIFIC GRAVITY @ 60 °F	0.8340
FLASH (P-M), °C	201
POUR POINT, °F	-48
VISCOSITY:	
cSt @ 40 °C	70.67
cSt @ 100 °C	13.28
VISCOSITY INDEX	193
CCS, Cp MAX @ (°C)	6200