



## **RUGGED EURO 75W90 GEAR OIL**

Rugged EURO 75W90 is a premium quality, semi-synthetic gear lubricant with a high VI to provide continued protection in extreme temperature operations. Rugged EURO 75W90 meets API GL-4 specifications, and exceeds all specified shear stability requirements for manual transmission fluids. EURO 75W90 is also suitable for full service refill, rebuild, or factory fill, where a GL-4 gear oil is required.

### **Applications:**

- Where API Service GL-4 is recommended.
- GL-4 denotes lubricants intended for axles with spiral bevel gears operating under moderate to severe conditions of speed and load or axles with hypoid gears operating under moderate speeds and loads.
- These oils may be used in selected manual transmissions and transaxle applications where MT-1 specification is not suitable.

### **Advantages:**

- Extreme shear stability.
- Longer gear life.
- Excellent resistance against foaming.
- Excellent rust and corrosion protection for gears and bearings.
- High Viscosity Index for extreme temperature ranges, and superior low temperature performance.
- Enhanced extreme pressure properties.
- Improves fuel mileage due to less resistance.
- Good oxidation stability as performed in the L-60-1 tests.

<b>TYPICAL PROPERTIES</b>		
SAE Grade		75w90
Specific Gravity (g/ml)	ASTM D-4052	.87
Flash Point °C	ASTM D-9	200
Pour Point °C	ASTM D-97	-12
Viscosity cSt		
@ 40°C	ASTM D-445	80.0
@ 100°C	ASTM D-445	14.5
Viscosity Index	ASTM D-2270	190
CCS @ -25°C	ASTM D-5293	6000 cP Max

**A SUPERIOR PRODUCT BY COLORADO PETROLEUM 5-14-2013 TH**