



SILVER STATE FULLY SYNTHETIC MOTOR OILS

SILVER STATE FULLY SYNTHETIC MOTOR OILS synthetic base stocks and robust additive packages provide the maximum level of protection against engine wear, rust, corrosion, oxidation and thermal breakdown. It also includes a special viscosity index improver and pour point depressant designed to provide a high degree of protection under severe temperature and operating conditions.

SPECIFICATIONS

- Surpasses API service classification SN Plus**.
- Meets or exceeds the U.S. and Japanese (JASO) requirements for valve train wear protection.
- Meets or exceeds Energy Resource Conserving, ILSAC GF-5**
- Exceeds car manufacturer's requirements for maintaining warranty validity.
- Meets or exceeds the latest automobile manufacturer's recommendations.
- ***SAE 0w20, SAE 5w-30 dexos1® Gen 2 Licensed**
- **SAE 5W-30 Euro** meets performance requirements of BMW Longlife-01, Mercedes Benz MB 229.5, Volkswagen VW 502 00/505 00 and API SL.
- **SAE 5w-40 Euro** meets or exceeds BMW Longlife-01, Mercedes Benz MB 229.3, 229.5, Volkswagen VW 502 00/505 00, Porsche, API SM, ACEA A3/B4 and A5/B5.

SILVER STATE FULLY SYNTHETIC MOTOR OILS provide an extra margin of safety for car owners who occasionally exceed prescribed drain intervals.

Note:

Warranty protection requires following manufacturers recommended drain intervals and viscosity grade.

TYPICAL PROPERTIES						
SAE GRADE	0W20*	5W20	5W30*	5W30Euro	5W40	10W30
ENERGY CONSERVING	YES	YES	YES	No	No	YES
SPECIFIC GRAVITY @ 60 °F	.846	.85	.86	.86	.85	.87
FLASH, °C	210	210	210	210	210	238
POUR POINT, °F	-50	-36	-36	-36	-34	-34
VISCOSITY:						
cSt @ 40 °C	44.6	60	62	71	86	66
cSt @ 100 °C	8.5	9	11	12.3	14.2	11.2
VISCOSITY INDEX	170	127	159	171	171	147
CCS, Cp MAX	6200	6600	6600	6600	6600	7000
@ (°C)	-35	-30	-30	-30	-30	-25

*0w20, 5w-30 dexos1® Gen 2 Licensed

** Except 5W-30 and 5W-40 European Formula

A SUPERIOR PRODUCT BY COLORADO PETROLEUM JDS 08 23 2018